

STATIC ELECTRIC LIFT PLATFORM

The HIW2.0EU is a Static Electric Lift Platform that can be used for many purposes including raising and lowering pallets.

It has a low profile, just 190mm, so it can virtually eliminate the need for a pit. Suitable for production piece work, or where repetitive bending and lifting operations need to be eliminated, resulting in a happier and more productive work force.

Supplied with a remote power pack, fitted with a pedestal unit leading to the controls - up, down and a safety stop button. There is a further safety feature, an all round safety bar perimeter fitted to the table top, designed to stop descent when it comes into contact with any obstruction.

Robust construction and a Powerful 0.75kW lifting motor giving a fast lift speed of approx. 40mm per second.

240 volt AC with 3 pin plug

European electronic controlling system

Confirms to EN1570 and BSEN60204-1

LOAD CAPACITY	1000kg
TABLE TOP SIZE	1300x800mm
MAXIMUM TABLE HEIGHT	1010mm
MINIMUM TABLE HEIGHT	190mm
LIFTING TIME	25 Seconds
LIFTING SPEED WITH LOAD	40mm / Second
LOWERING SPEED WITH LOAD	35mm / Second
MOTOR - 3 PHASE AC380v/50hz	0.75kW
UNIT WEIGHT	220kg

